

Jasper Morrison urinal, rim flushing, Fully Concealed

ILLUSTRATED

- E6215** Jasper Morrison bowl urinal rim flushing, back inlet and concealed waste
- E6227** Urinal syphon connector with 75mm water seal, and 40mm outlet
- K7106** Urinal Connecting set
- A7001** Sensorflow 21 urinal flush, high pressure valve, panel mounted, mains

OPTIONS

- R0163** Prosys urinal frame for use with Sensorflow (specific urinals only)
- S6120** Urinal division Vitreous China with hanger and screw



ILLUSTRATED PRODUCT DETAILS

Weights

- E6215** 17.00 KG
- E6227** 0.50 KG
- K7106** 0.09 KG
- A7001** 1.51 KG

Materials

- E6215** Vitreous China
- E6227** Plastic
- K7106** Plastic
- A7001** Chrome Plated Brass

Finishes

- E6215** White (01)
- E6227** Neutral / No Finish (67)
- K7106** Neutral / No Finish (67)
- A7001** Chrome (AA)

Designer

Jasper Morrison

FINISH OPTIONS



Standards

Vitreous china to BS 3402

Special Notes

Please click the [Specify this] button and then configure the bowl by adding one of the Sensorflow 21 electronic urinal flushing products. Mains versions can power up to 5 link flushing valves or the battery versions can be independent. Please refer to Sensorflow 21 compact urinal flushing device pages. Then add as many urinals assembly types: mains/linked/battery, as needed in the room schedule. Not suitable for flushing from a cistern. Please note minimum working pressure required is 1 bar dynamic. A WRAS approved DC interrupter should be fitted to satisfy the UK regulations.

